QuickTask™ Mop

Flat mop with polyester knitted microfiber face

The QuickTask™ range consists of a variety of flat mops that can be easily attached to a choice of flat mop frames and handle assemblies.

The TASK0400 mop is manufactured from 100% knitted, cleanroom laundered microfiber polyester making it the cleanest mop in the range with extremely low levels of particulates. The tubular knit loops make cleaning of cove bases and ceiling/wall joints easier than with standard flat mops. The looped construction is very sorbent, and the mop can be used for application of a wide range of solutions, and to mop dry already wet surfaces.

Features	Benefits
Tubular knit loops	• Conform to any shape making it especially suitable for covering bases and wall/floor joints • Very absorbent and drip-free • Compatible with most common solutions, solvents and disinfectants
Manufactured from cleanroom laundered polyester	• Very low level of particulates • Cleanest and most durable mop cover in the range
Microfiber construction	• Provide high levels of sorbency and good performance drying wet surfaces

Contact us:
info@contecinc.com
cleanroom.contecinc.com

Contec, Inc.
Spartanburg, SC 29303 USA
tel: +1-864-503-8333

CONTEC® CLEANROOM

Part No.	Description	Size	Packaging
TASK0400	QuickTask Mop Polyester knitted microfiber	16" x 5" (406 x 130 mm)	10/bag; 5 bags/case
2740	QuickTask Mop Frame Polypropylene	16" x 4.25" (41 x 11 cm)	1/case
2699P	QuickTask Magnetic Mop Frame Polypropylene	15.5" x 3.75" (40 x 10 cm)	1/case
2906	QuickTask Magnetic Mop Frame Stainless steel	15.5" x 3.75" (40 x 10 cm)	1/case

Product Information

Mop material	• 100% polyester microfiber loop; woven polyester backing; Woven polyester hemmed edge
Mop construction	• Multilayer sewn lamination/sealed border
Packaging materials	• Outer bags (OB1, OB2), low density polyethylene (LDPE) ♻ Case (CS), corrugated fiberboard (PAP) ♻
Chemical compatibility	• Compatible with a wide range of chemicals and disinfectants
Environment	• ISO 4-8 Grade A/B for sterile, C/D for nonsterile

TASK0400

Recycle Symbols

PET	HDPE	LDPE	PP	PAP
♻ 1	♻ 2	♻ 4	♻ 5	♻ 20

Contact us:
info@contecinc.com
cleanroom.contecinc.com

Contec, Inc.
Spartanburg, SC 29303 USA
tel: +1-864-503-8333

CONTEC®
CLEANROOM

Technical Data

Attribute (units)	Typical Value	Test Method
Mop weight, dry; (g)	136	CTM004-03
Sorbent capacity; (mL/mop)	250	CTM004-03
Particles $\geq$ 0.5µm; ($\times 10^6$/mop)	3.81	CTM006-01
Fibers $\geq$ 100µm; ($\times 10^3$/mop)	0.07	CTM006-01
Mop coverage; ft^2 (m^2)		CTM037-01
S-Curve	375 (35)	
Place and Pull	200 (19)	
Mop frames	2906, 2699P, 2740	

Packaging	EA/OB1	OB1/OB2	OB2/CS	EA/CS
TASK0400	10	1	5	50

EA = each; OB = outer bag 1/2; CS = case

Notes
a) The data shown are typical values and should not be used as product specifications.
b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
c) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Test Methods
1. CTM = Refers to Contec Test Method.
2. Mop coverage data is based on mop head applying solution such that the mopped surface is visibly wetted across the full mop path with no dry streaking observed, under controlled conditions.
   It is the responsibility of the user to determine appropriate coverage to ensure surfaces are visibly wet for the contact time required for their specific solution.

Contact us:
info@contecinc.com
cleanroom.contecinc.com

Contec, Inc.
Spartanburg, SC 29303 USA
tel: +1-864-503-8333

CONTEC
CLEANROOM