

EliminatR® Pillow

Disposable cleanroom spill control pillow

The EliminatR® Pillow is a disposable cleanroom sorbent pillow designed for large spill pickup or as a drip-catching pad under equipment.



The pillow is performance engineered utilizing 100% polyester knitted fabric, which has excellent sorbency for aqueous spills and superior holding ability for oils. The outer covering is made from Contec's Quiltec® I fabric, a durable two-ply polyester fabric which means the pillow is designed to be low in particles as well as sorbent. It is free of any cellulosic contaminants and is recommended for use in ISO Class 6 and above cleanrooms.

Compatible with gamma, ethylene oxide, vaporized hydrogen peroxide, and autoclave sterilization, the EliminatR® Pillow is ideal for large spill pick up or as a drip-catching pad under equipment. Designed for use in conjunction with the EliminatR® Sock.



Features	Benefits
Performance engineered	<ul style="list-style-type: none"> Utilizing 100% polyester knitted fabric, which has excellent sorbency for aqueous spills and superior holding ability for oils
Acid resistance	<ul style="list-style-type: none"> Provides superior holding ability for oils and acids
Outer covering is made from Contec's Quiltec® I fabric	<ul style="list-style-type: none"> Durable two-ply polyester fabric which means the pillow is low in particles and high in sorbency Compatible with gamma, ethylene oxide, vaporized hydrogen peroxide, and autoclave sterilization

Part No.	Description	Size	Packaging
ELRPIL	EliminatR Pillow	12" x 12" x 1" (305 x 305 x 25 mm)	1/bag; 12 bags/case

Product Information	
Material	• 100% polyester
Construction	• Interlock knit, no-run
Environment	• ISO 6-8 Grade C/D
Packaging materials	• Outer bags (OB1, OB2), low density polyethylene (LDPE)  Case (CS), corrugated fiberboard (PAP) 



Technical Data		
Attribute (units)	Typical Value	Test Method
Basis weight, nominal; (g/m ²)	372	Contec Method
Sorbent capacity; (mL/each)	2409	IEST-RP-CC004.3, Sec. 7.1
Sorptive rate; (seconds)	<1	
Non-volatile residue, NVR		IEST-RP-CC004.3, Sec. 6.1.1
In deionized water; (g/m ²)	0.033	
In isopropyl alcohol; (g/m ²)	0.031	

Recycle Symbols

- PET 
- HDPE 
- LDPE 
- PP 
- PAP 

Packaging	EA/OB1	OB1/OB2	OB2/CS	EA/CS
ELRPIL	1	1	12	12

EA = each; OB = outer bag; CS = case

Notes

- a) The data shown are typical values and should not be used as product specifications.
- b) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- c) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Test Methods

- 1. CTM = Contec Test Method
- 2. IEST-RP-CC004.3 = Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments, Institute of Environmental Sciences and Technology, Rolling Meadows IL.